AD-A263 011

SAARL Report Jo. 93-10



Sound Attenuation Characteristics of the Standard DH-132A and SPH-4 Helmets Worn in Combination with Standard Issue Earplugs

By

Ben T. Mozo Linda S. Barlow Barbara A. Murphy



Sensory Research Division

January 1993



4 16 The Approved for public release; distribution unlimited.

United States Army Aeromedical Research Laboratory Fort Rucker, Alabama 36362-5292

<u>Notice</u>

<u>Oualified requesters</u>

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Human use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:

RICHARD R. LEVINE

LTC, MS

Director, Sensory Research Division

Released for publication:


ROGER W. WILEY, O.D., Ph.D.

Chairman, Scientific Review Committee DAVID H. KARNEY Colonel, MC, SFS

Commanding

Table of contents

Introduction					
Methods and instrumentation	3				
Results and discussion	5				
Conclusions					
References	9				
Appendixes A. Photographic display of SPH- standard Army issue earplugs B. Photographic display of DH-1 standard Army issue earplugs C. Manufacturers' list	32A helmet with				
List of tab	<u>les</u>				
 Mean real-ear attenuation and sta results of the DH-132A and SPH- combination with three types of 	4 helmet used in				
 Mean real-ear attenuation and sta results of three earplugs used of the DH-132A and SPH-4 helmet 	in the evaluation				
3. Estimated effective exposure leve aviators wearing the SPH-4 helm with three types of earplugs at while in noise levels produced aircraft	et in combination the pilot's position by various Army				
4. Estimated effective exposure leve combat vehicle crewmen wearing in combination with three types in noise levels produced by var combat vehicles	the DH-132A helmet of earplugs while rious ground				
List of figu	res				
1. Real-ear attenuation test system standard S12.6	measurement . According For				
DTIC QUALITY INSPECTED 4	Disc 1AB [] U. mpounced [] U tito are				
	By Dr.t ibation/				
1	Availability Codes				
	Dist Avail and for Special				



Introduction

The Health Hazard Assessment (HHA) of Army systems usually requires a review of noise and hearing protection associated with the systems used. Hearing protection for crews in combat vehicles is specified to be the DH-132A and, in some cases where noise levels are extremely high, earplugs are worn in combination with the helmet in order to provide adequate protection. Hearing protection for Army helicopter crewmembers is the SPH-4 helmet with a few exceptions. The attenuation data used for the HHA are measured at this Laboratory. This report incorporates the results of attenuation measurements of the SPH-4 and DH-132A helmets worn in combination with the standard Army issue earplugs. Earplugs used in the study were the single flange, triple flange, and yellow/white foam plug.

Methods and instrumentation

Real-ear sound attenuation measurements were completed on the standard DH-132A and SPH-4 helmets worn in combination with standard Army issue earplugs (see Appendixes). The measurements utilized the procedures described in ANSI Standard S12.6-1984, "Method for the measurement of the real-ear attenuation of hearing protectors." Figure 1 shows the test system used in determining the attenuation characteristics of the protective devices. Stimuli required by the S12.6 method are 1/3 octave bands of noise with center frequencies at 125, 250, 500, 1000, 2000, 3150, 4000, 6300, and 8000 Hz. The noise bands were presented to the listener in a hard-walled room which provided a nondirectional sound field.

Ten listeners, male and female, with normal hearing were selected, in accordance with ANSI S3.6-1989 (R1969), to evaluate the real-ear attenuation characteristics of the devices. Real-ear attenuation was defined as the difference in auditory threshold of occluded (wearing the helmet) and unoccluded (not wearing the helmet) measurements. of adjustments psychophysical procedure was used to measure the hearing threshold of the subjects. Subjects, one at a time, were seated in the sound room with their heads placed at a fixed location in space. A key pad, which is controlled by the subject, was used to increase or decrease the stimulus level during the experiment. The subjects were instructed to adjust the stimulus level to their auditory threshold for four separate trials for each of the test frequencies while wearing and not wearing the hearing protector. The average stimulus level of the four trials at each test frequency was used as

REAL-EAR ATTENUATION TEST SYSTEM MEASUREMENT STANDARD \$12.6




Figure 1. Real-ear attenuation test system measurement standard S12.6.

threshold for that test condition. The attenuation for each of the test frequencies was measured for three fittings of the hearing protector for each of the subjects in the evaluation. The attenuation for each fitting of the 10 subjects was used to calculate mean and standard deviation values for each of the test frequencies.

Real-ear attenuation characteristics were measured on three earplugs, one foam and two premolded, in combination with a DH-132A and an SPH-4 helmet. Subjects were provided training in the proper procedures of fitting the earplugs and the helmet combination. Each device was fitted by the subject under the supervision of the experimenter. Earplug and helmet size were determined by the experimenter.

The test sequence was designed to allow measurement of the helmet/earplug combination and the earplug only. The fit of the earplug was the same for both measurements. A single unoccluded measure was paired with each of the two occluded measures. Each of the three test measurements were repeated three times for each subject.

Results and discussion

The results of the attenuation measurements are shown in Tables 1 and 2. As expected, these data indicate improvements in attenuation for the helmet/earplug combination when compared to attenuation results while wearing earplugs only.

The noise hazard that an individual is exposed to may be estimated by combining noise level and sound attenuation measurements to determine noise at the ear. This estimated effective exposure level (EEL) is an indicator of the hearing protective capability of the helmet and earplugs for the noise environment in which it is to be used. Use of the EEL provides insight into the hearing protector's capability when used in a particular noise environment. DoD Instruction 6055.12, "Hearing Conservation," states that steady noise of dBA or greater is a naidered hazardous, regardless of duration of exposure.

Table 3 shows the EEL of aviators wearing the SPH-4 helmet in combination with three types of earplugs rile flying in various Army aircraft. EELs for each of the hearing protective devices evaluated are well below the 85 dBA criteria for all aircraft indicated. Table 4 shows the EELs of combat vehicle crewmen wearing the DH-132A helmet in combination with three types of earplugs for noise levels produced by the M3, M1 and the M113. EELs for each of the hearing protective devices evaluated exceed the 85 dBA criteria for the M113 and M3 except the DH-132A/foam earplug combination. The EELs for the M1 are below the 85 dBA criteria for all DH-132A/earplug combinations.

Mean real-ear attenuation and standard deviation results in dB of the DH-132A and SPH-4 helmets used in combination with three types of earplugs

Test frequencies in hertz

		125	250	500	1000	2000	3150	4000	6300	8000
DH-132A w/triple flange plug	Mean S.D.	32.0 5.3	37.1 6.0	40.2 5.4	34.9 5.2	34.0 4.8	43.1 4.5	45.1 4.8	47.4 6.0	50.2 3.6
SPH-4 w/triple flange plug	Mean S.D.	30.6 6.6	33.3 5.9	36.2 6.8	32.0 4.0	38.6 4.3	49. 0 4. 0	52.2 3.8	53.6 4.5	53.7 3.6
DH-132A w/single flange plug	Mean S.D.	27.6 5.9	34.2 6.3	34.0 6.4	32.0 3.5		47.9 5.3	50.7 4.8	52.2 5.8	50.8 5.8
SPH-4 w/single flange plug	Mean S.D.	27.5 4.9	29.5 5.5	34.4 6.0	32.1 5.5	38.3 4.4	49.6 5.0	53.6 5.6	55.3 5.5	54.7 4.0
DH-132A w/foam plug	Mean S.D.	33.9 6.0	40.7 6.9	47.0 7.8	38.7 5.1	38.1 4.2	48.7 5.3	52.7 5.4	53.9 4.9	55.4 4.7
SPH-4 w/foam plug	Mean S.D.	32.7 7.2	36.9 7.2	42.4 7.9	37.2 7.6	37.5 4.1	50.7 5.9	52.7 6.1	55.5 5.2	54.8 4.5

Table 2.

Mean real-ear attenuation and standard deviation results in dB of three earplugs used in the evaluation of the DH-132A and SPH-4 helmets

Test	frequenc	es in	hertz
1696	TICAMBIL.	res III	1167 62

		125	250	570	1000	2000	3150	4000	6300	8000
*Triple	Mean	21.5	20.3	21.5	23.0	27.8	32.0	31.3	36.2	38.0
flange plug	S.D.	6.5		7.0	4.7	5.0	9.2	10.5	9.3	7.3
**Triple flange plug	Mean S.D.	21.2	21.0	20.8	21.0 4.7	27.6 6.3	30.0 9.3	27.9 10.3	35.0 9.4	36.2 9.6
*Single	Mean	19.2	19.3	19.4	19.9	26.5	20.9	26.1	28.9	27.0
flange plug	S.D.	6.6	6.1	7.0	4.7	5.0	5.2	5.3	7.0	6.1
**Single	Mean	20.7	19.2	20.5	21.4	26.7	28.8	26.0	29.9	27.9
flange plug	S.D.	4.6	4.9	5.1	4.5	3.5	5.0	4.2	7.3	7.3
*Foam	Mean	28.1	28.1	31.0	29.4	31.1	39.9	40.2	41.3	42.8
plug	S.D.	8.8	8.0	7.8	6.0	5.0	4.1	3.2		3.6
**Foam	Mean	27.8	26.6	29.2	27.8	30.4	39.0	39.3	41.0	41.2
plug	S.D.	7.3	6.1	7.8	6.4	4.9	3.9	4.6	3.5	

^{*}DH-132A helmet

^{**}SPH-4 helmet

Estimated effective exposure level (EEL) in dBA of aviators wearing the SPH-4 helmet in combination with three types of earplugs

Table 3.

at the pilot's position while in noise levels
produced by various Army aircraft

Pretector	UH-60A 120 kn	CH-47C 100_kn	AH-1S 100 kn	OH-58 cruise	UH-1H _100 kn
			200 7	<u> </u>	
SPH-4 with triple flange plug	72.6	77.5	70.2	65.7	70.7
SPH-4 with single flange plug	75.3	78.4	71.5	67.4	71.9
SPH-4 with foam plug	70.4	77.3	68.8	63.5	68.8

Table 4.

Estimated effective exposure level (EEL) in dBA of combat vehicle crewmen wearing the DH-132A helmet in combination with three types of earplugs while in noise levels produced by various ground combat vehicles

Protector	M3 30 mph	M1E1 32 mph	M113 30 mph
Triple flange plug	85.5	78.5	91.3
Single flange plug	89.8	82.4	94.7
Foam plug	83.2	76.6	89.4

Conclusions

The foam marplug combined with helmet provides highest sound attenuation while the single flange combined with helmet provides lowest sound attenuation of the hearing protectors evaluated. Sound attenuation characteristics of the SPH-4/earplug combination provides adequate hearing protection for Army aviation noise environments. DH-132A/foam earplug combination provides adequate hearing protection for M1E1 and M3 noise environments. Noise levels produced by the M113 at 30 mph exceed protective capabilities of any of the hearing protector conditions evaluated.

References

- American National Standards Institute. 1989. Specification for audiometers. S3.6-1989 (R1969).
- American National Standards Institute. 1984. Method for the measurement of the real-ear attenuation of hearing protectors. S12.6-1984.
- Department of Defense. 1991. <u>Hearing conservation</u>. Washington, DC: Department of the Army. Department of Defense Instruction 6055.12.

Appendix A

Photographic display of SPH-4 helmet with standard Army issue earplugs



Appendix B

Photographic display of DH-132A helmet with standard Army issue earplugs



Appendix C

Manufacturers' list

Altec Lansing Corporation 1515 South Manchester Avenue Anaheim, CA 92803

B&K Instruments Inc. 5111 West 164th Street Cleveland, OH 44142

Tracoustics, Inc. P.O. Box 3610 Austin, TX 78764

Initial distribution

Commander, U.S. Army Natick Research,
Development and Engineering Center
ATTN: SATNC-MIL (Documents
Librarian)
Natick, MA 01760-5040

U.S. Army Communications-Electronics Command ATTN: AMSEL-RD-ESA-D Fort Monmouth, NJ 07703

Commander/Director
U.S. Army Combat Surveillance
and Target Acquisition Lab
ATTN: DELCS-D
Fort Monmouth, NJ 07703-5304

Commander
10th Medical Laboratory
ATTN: Audiologist
APO New York 09180

Naval Air Development Center Technical Information Division Technical Support Detachment Warminster, PA 18974

Commanding Officer, Naval Medical Research and Development Command National Naval Medical Center Bethesda, MD 20814-5044

Deputy Director, Defense Research and Engineering ATTN: Military Assistant for Medical and Life Sciences Washington, DC 20301-3080

Commander, U.S. Army Research Institute of Environmental Medicine Natick, MA 01760 Library
Naval Submarine Medical Research Lab
Box 900, Naval S b Base
Groton, CT 06349-5900

Director, U.S. Army Human
Engineering Laboratory
ATTN: Technical Library
Aberdeen Proving Ground, MD 21005

Commander
Man-Machine Integration System
Code 602
Naval Air Development Center
Warminster, PA 18974

Commander
Naval Air Development Center
ATTN: Code 602-B (Mr. Brindle)
Warminster, PA 18974

Commanding Officer Armstrong Laboratory Wright-Patterson Air Force Base, OH 45433-6573

Director
Army Audiology and Speech Center
Walter Reed Army Medical Center
Washington, DC 20307-5001

Commander, U.S. Army Institute of Dental Research ATTN: Jean A. Setterstrom, Ph. D. Walter Reed Army Medical Center Washington, DC 20307-5300

Commander, U.S. Army Test and Evaluation Command ATTN: AMSTE-AD-H Aberdeen Proving Ground, MD 21005 Naval Air Systems Command Technical Air Library 950D Room 278, Jefferson aza II Department of the Navy Washington, DC 20361

Director
U.S. Army Ballistic
Research Laboratory
ATTN: DRXBR-OD-ST Tech Reports
Aberdeen Proving Ground, MD 21005

Commander
U.S. Army Medical Research
Institute of Chemical Defense
ATTN: SGRD-UV-AO
Aberdeen Proving Ground,
MD 21010-5425

Commander, U.S. Army Medical Research and Development Command ATTN: SGRD-RMS (Ms. Madigan) Fort Detrick, Frederick, MD 21702-5012

Director
Walter Reed Army Institute of Research
Washington, DC 20307-5100

HQ DA (DASG-PSP-O) 5709 Leesburg Pike Falls Church, VA 22041-3258

Harry Diamond Laboratories ATTN: Technical Information Branch 2800 Powder Mill Road Adelphi, MD 20783-1197

U.S. Army Materiel Systems
Analysis Agency
ATTN: AMXSY-PA (Reports Processing)
Aberdeen Proving Ground
MD 21005-5071

U.S. Army Ordnance Center and School Library Simpson Hall, Building 3071 Aberdeen Proving Ground, MD 21005

U.S. Army Environmental
Hygiene Agency
Building E2100
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research and Development Center Aberdeen Proving Ground, MD 21010--5423

Commander
U.S. Army Medical Research
Institute of Infectious Disease
SGRD-UIZ-C
Fort Detrick, Frederick, MD 21702

Director, Biological Sciences Division Office of Naval Research 600 North Quincy Street Arlington, VA 22217

Commander
U.S. Army Materiel Command
ATTN: AMCDE-XS
5001 Eisenhower Avenue
Alexandria, VA 22333

Commandant
U.S. Army Aviation
Logistics School ATTN: ATSQ-TDN
Fort Eustis, VA 23604

Headquarters (ATMD)
U.S. Army Training
and Doctrine Command
ATTN: ATBO-M
Fort Monroe, VA 23651

Structures Laboratory Library USARTL-AVSCOM NASA Langley Research Center Mail Stop 266 Hampton, VA 23665

Naval Aerospace Medical Institute Library Building 1953, Code 03L Pensacola, FL 32508-5600

Command Surgeon
HQ USCENTCOM (CCSG)
U.S. Central Command
MacDill Air Force Base FL 33608

Air University Library
(AUL/LSE)
Maxwell Air Fore Base, AL 36112

U.S. Air Force Institute of Technology (AFIT/LDEE) Building 640, Area B Wright-Patterson Air Force Base, OH 45433

Henry L. Taylor Director, Institute of Aviation University of Illinois-Willard Airport Savoy, IL 61874

Chief, National Guard Bureau ATTN: NGB-ARS (COL Urbauer) Room 410, Park Center 4 4501 Ford Avenue Alexandria, VA 22302-1451

Commander
U.S. Army Aviation Systems Command
ATTN: SGRD-UAX-AL (LTC Gillette)
4300 Goodfellow Blvd., Building 105
St. Louis, MO 63120

U.S. Army Aviation Systems Command Library and Information Center Branch ATTN: AMSAV-DIL 4300 Goodfellow Boulevard St. Louis, MO 63120

Federal Aviation Administration Civil Aeromedical Institute Library AAM-400A P.O. Box 25082 Oklahoma City, OK 73125

Commander
U.S. Army Academy
of Health Sciences
ATTN: Library
Fort Sam Houston, TX 78234

Commander
U.S. Army Institute of Surgical Research
ATTN: SGRD-USM (Jan Duke)
Fort Sam Houston, TX 78234-6200

AAMRL/HEX Wright-Patterson Air Force Base, OH 45433

John A. Dellinger, Southwest Research Institute P. 0. Box 28510 San Antonio, TX 78284

Product Manager Aviation Life Support Equipment ATTN: AMCPM-ALSE 4300 Goodfellow Boulevard St. Louis, MO 63120-1798

Commander
U.S. Army Aviation
Systems Command
ATTN: AMSAV-ED
4300 Goodfellow Boulevard
St. Louis, MO 63120

Commanding Officer Naval Biodynamics Laboratory P.O. Box 24907 New Orleans, LA 70189-0407

Assistant Commandant
U.S. Army Field Artillery School
ATTN: Morris Swott Technical Library
Fort Sill, OK 73503-0312

Commander
U.S. Army Health Services Command
ATTN: HSOP-SO
Fort Sam Houston, TX 78234-6000

U.S. Army Dugway Proving Ground Technical Library, Building 5330 Dugway, UT 84022

U.S. Army Yuma Proving Ground Technical Library Yuma, AZ 85364

AFFTC Technical Library 6510 TW/TSTL Edwards Air Force Base, CA 93523-5000

Commander Code 3431 Naval Weapons Center China Lake, CA 93555

Aeromechanics Laboratory
U.S. Army Research and Technical Labs
Ames Research Center, M/S 215-1
Moffett Field, CA 94035

Sixth U.S. Army ATTN: SMA Presidio of San Francisco, CA 94129 Commander
U.S. Army Aeromedical Center
Fort Rucker, AL 36362

U.S. Air Force School
of Aerospace Medicine
Strughold Aeromedical Library Technical
Reports Section (TSKD)
Brooks Air Force Base, TX 78235-5301

Dr. Diane Damos
Department of Human Factors
ISSM, USC
Los Angeles, CA 90089-0021

U.S. Army White Sands
Missile Range
ATTN: STEWS-IM-ST
White Sands Missile Range, NM 88002

U.S. Army Aviation Engineering
Flight Activity
ATTN: SAVTE-M (Tech Lib) Stop 217
Edwards Air Force Base, CA 93523-5000

Ms. Sandra G. Hart Ames Research Center MS 262-3 Moffett Field, CA 94035

Commander, Letterman Army Institute of Research ATTN: Medical Research Library Presidio of San Francisco, CA 94129

Commander
U.S. Army Medical Materiel
Development Activity
Fort Detrick, Frederick, MD 21702-5009

Commander
U.S. Army Aviation Center
Directorate of Combat Developments
Building 507
Fort Rucker, At 36362

U. S. Army Research Institute Aviation R&D Activity ATTN: PERI-IR Fort Rucker, AL 36362

Commander
U.S. Army Safety Center
Fort Rucker, AL 36362

U.S. Army Aircraft Development Test Activity ATTN: STEBG-MP-P Cairns Army Air Field Fort Rucker, AL 36362

Commander U.S. Army Medical Research and Development Command ATTN: SGRD-PLC (COL Schnakenberg) Fort Detrick, Frederick, MD 21702

MAJ John Wilson TRADOC Aviation LO Embassy of the United States APO New York 09777

Netherlands Army Liaison Office Building 602 Fort Rucker, AL 36362

British Army Liaison Office Building 602 Fort Rucker, AL 36362

Italian Army Liaison Office Building 602 Fort Rucker, AL 36362

Directorate of Training Development Building 502 Fort Rucker, AL 36362

Chief USAHEL/USAAVNC Field Office P. O. Box 716 Fort Rucker, AL 36362-5349 Commander U.S. Army Aviation Center and Fort Rucker ATTN: ATZQ-CG Fort Rucker, AL 36362

Chief
Test & Evaluation Coordinating Board
Cairns Army Air Field
Fort Rucker, AL 36362

MAJ Terry Newman Canadian Army Liaison Office Building 602 Fort Rucker, AL 36362

German Army Liaison Office Building 602 Fort Rucker, AL 36362

LTC Patrice Cottebrune French Army Liaison Office USAAVNC (Building 602) Fort Rucker, AL 36362-5021

Australian Army Liaison Office Building 602 Fort Rucker, AL 36362

Dr. Garrison Rapmund 6 Burning Tree Court Bethesda, MD 20817

Commandant, Royal Air Force Institute of Aviation Medicine Farnborough Hampshire GU14 6SZ UK

Commander
U.S. Army Biomedical Research
and Development Laboratory
ATTN: SGRD-UBZ-I
Fort Detrick, Frederick, MD 21702

Defense Technical Information Cameron Station, Building 5 Alexandra, VA 22304-6145 Commander, U.S. Army Foreign Science and Technology Center AIFRTA (Davis) 220 7th Street, NE Charlottesville, VA 22901-5396

Director, Applied Technology Laboratory USARTL-AVSCOM ATTN: Library, Building 401 Fort Eustis, VA 23604

U.S. Air Force Armament
Development and Test Center
Eglin Air Force Base, FL 32542

Commander, U.S. Army Missile
Command
Redstone Scientific Information Center
ATTN: AMSMI-RD-CS-R
/ILL Documents
Redstone Arsenal, AL 35898

Dr. H. Dix Christensen Bio-Medical Science Building, Room 753 Post Office Box 26901 Oklahoma City, OK 73190

Director

Army Personnel Research Establishment Farnborough, Hants GU14 6SZ UK

U.S. Army Research and Technology Laboratories (AVSCOM) Propulsion Laboratory MS 302-2 NASA Lewis Research Center Cleveland, OH 44135

Col. Otto Schramm Filho c/o Brazilian Army Commission Office-CEBW 4632 Wisconsin Avenue NW Washington, DC 20016 Dr. Eugene S. Channing 7985 Schooner Court Frederick, MD 21701-3273

LTC Gaylord Lindsey (5)
USAMRDC Liaison at Academy
of Health Sciences
ATTN: HSHA-ZAC-F
Fort Sam Houston, TX 78234

Aviation Medicine Clinic TMC #22, SAAF Fort Bragg, NC 28305

Dr. A. Kornfield, President Biosearch Company 3016 Revere Road Drexel Hill, PA 29026

NVEOD AMSEL-RD-ASID (Attn: Trang Bui) Fort Belvior, VA 22060

CA Av Med HQ DAAC Middle Wallop Stockbridge Hants S020 8DY UK

Commander and Director
USAE Waterways Experiment Station
ATTN: CEWES-IM-MI-R
Alfrieda S. Clark, CD Dept.
3909 Halls Ferry Road
Vicksburg, MS 39180-6199

Mr. Richard Thornley
ILS Manager, APACHE
Box 84
Westland Helicopters Limited
Yeovil, Somerset BA202YB UK

Dr. Christine Schlichting Behavioral Sciences Department Box 900, NAVUBASE NLON Groton, CT 06349-5900